

## Claims:

1. A convertible vehicle (1) with a moving roof (3) having a flexible cover (5), in which the cover (5) is engaged underneath by at least one strap (9), following essentially the course of the roof when the roof (3) is closed, which is secured on support structure (7; 8) arranged across the roof (3),  
5                   **characterized in that** an end (9a) of the at least one strap (9) passes through a slit recess (10) of said support structure (7; 8) and is secured against pulling out from the slit recess by an end thickening (11) on the at least one strap (9).
2. A convertible vehicle (1) according to Claim 1,  
                  **characterized in that** the end thickening (11) is formed by a loop of the strap (9) stitched around and enclosing a piping.
3. A convertible vehicle (1) according to Claim 1,  
                  **characterized in that** said slit recess (10) is arranged in a front transverse support of said roof support structure, a so-called roof strut (7).
4. A convertible vehicle (1) according to Claim 1,  
                  **characterized in that** that the slit recess (10) has a widening (13) on one end that receives the end thickening (11) for installation.
5. A convertible vehicle (1) according to Claim 4,  
                  **characterized in that** the widening (13) has an essentially round shape with a diameter only slightly greater than that of the end thickening (11).
6. A convertible vehicle (1) according to Claim 1,  
                  **characterized in that** a strap (9) is assigned to each side of the vehicle.
7. A convertible vehicle (1) according to Claim 1,  
                  **characterized in that** said at least one strap (9) is free of holes.

8. A convertible vehicle (1) according to one of the Claim 1,  
**characterized in that** the front and rear strap ends (9a) are fastened the  
same way to different support structure (7, 8) of roof (3).

9. A moving roof (3) for a convertible vehicle (1) according to Claim 1.